



LIQUID WASTE HAULER INSPECTION CHECKLIST

- ☐ **Inspect the suction hoses and verify they are in good repair and not leaking. Tape used to seal leaks is not an acceptable repair.**
- ☐ **Inspect the waste tank, caps, covers, and valves and verify they are not leaking and in good repair.**
- ☐ **Inspect all outlet caps and make sure a chain or wire is connected between the cap and truck so it cannot be removed from the truck or lost.**
- ☐ **Inspect all tires and verify they have sufficient tread. Tires with too little tread or that are bald are not acceptable.**
- ☐ **Inspect all vehicle safety lights and verify that the headlights, brake lights, running lights, turn signals and hazard lights function properly. The lights on the carrier racks are included in this requirement.**
- ☐ **Inspect vehicle cleanliness and verify the truck is reasonably clean.**
- ☐ **Verify that a business name and current telephone number is clearly visible on the vehicle.**
- ☐ **Kitchen grease haulers need to show proof of a Department of Food and Agriculture permit for kitchen grease hauling (decal or copy of permit).**
- ☐ **Haulers offloading at the Orange County Sanitation District need to have a 4" sludge release line with a female quick coupler.**
- ☐ **Haulers must show evidence of the disposal station used for disposal or the method used to properly dispose of waste.**
- ☐ **Verify that 2 gallons of bleach are on board. Bleach is used to disinfect surfaces that are contaminated by spills and leaks.**
- ☐ **Portable toilet companies need to show the product used to deodorize toilets.**
- ☐ **Know basic sanitary laws and that offloading to manholes or other unapproved locations in Orange County is strictly prohibited.**