



LIQUID WASTE HAULER INSPECTION CHECKLIST

- ☐ **All suction hoses must be in good repair and not leaking. Duct tape used to seal leaks is not an acceptable repair.**
- ☐ **Inspect waste tank, caps, covers, valves, and verify they are not leaking and in good repair.**
- ☐ **Inspect all outlet caps and make sure a chain or wire is connected between the cap and truck so it cannot be removed from the truck.**
- ☐ **Inspect all tires and verify they have sufficient tread. Tires with too little tread or bald are not acceptable.**
- ☐ **Inspect all vehicle safety lights. Verify headlights, brake lights, running lights, turn signals and hazard lights function properly. The lights on the carrier racks are included in this requirement.**
- ☐ **Inspect vehicle cleanliness and verify the truck is reasonably clean.**
- ☐ **BUSINESS name and TELEPHONE number must be visible on driver side and passenger doors, with minimum 3" lettering.**
- ☐ **Kitchen grease haulers need to show proof of a Department of Food and Agriculture permit for kitchen grease hauling (decal or copy of permit).**
- ☐ **Vehicles offloading at OC Sanitation District must have 4" sludge release line with female quick coupler. Call 714-593-7434 to verify discharge requirements.**
- ☐ **Haulers must show evidence of the disposal station used for disposal or the method used to properly dispose of waste.**
- ☐ **Verify 2 gallons of disinfectant are on board vehicle. This product shall be used to disinfect surfaces which are contaminated by spills and leaks.**
- ☐ **Portable toilet companies shall verify product used to deodorize toilets.**
- ☐ **Offloading to manholes or other unapproved locations in Orange County is strictly prohibited.**